



| | |
|-------------------------------|--|
| Network Module Expansion Slot | 2 providing up to 64 bidirectional channels per slot |
| Type | Cirrus CM-1 format compatible |
| Sample Rate Selectable | 48 KHz or 96 kHz |
| Channels | Up to 64 bidirectional per Slot |
| AES50 Ports | 10 |
| Type | Neutrik etherCON with LED status indication |
| Sample Rate | 96 kHz |
| | |
| Dimensions | |
| Height | 96 mm |
| Width | 303 mm |
| Depth | 306 mm |
| Weight | Net 1.3 kg |
| | |
| Options | |
| KLARK TEKNIK KT-AES50 | AES50 Network Module with up to 48 Bidirectional Channels |
| KLARK TEKNIK KT-DANTE64 | Audinate Dante Network Module with up to 64 Bidirectional Channels |
| KLARK TEKNIK KT-MADI | MADI Network Module with up to 64 Bidirectional Channels |
| KLARK TEKNIK KT-USB | USB 2.0 Network Module with up to 48 Bidirectional Channels |



| | |
|----|-----------------|
| 種別 | オーディオシステムI/O |
| | AES50 prot拡張カード |
| 形式 | NEUTRON NB |
| 縮尺 | 1 / 5 |
| 作成 | 201706 |

C